

SUPPLEMENTAL BID BULLETIN

BID BULLETIN NO. 05-2021

This Bid Bulletin No. 05-2021 is issued to modify or amend portion of the bidding documents relative to the conduct of public bidding for the Supply and Delivery of Various Food Processing Equipment for the Cacao Processing and Processed Fruit Toll Packaging Shared Service Facilities (SSF) in Region 2 which was posted at the Philippine Government Electronic Procurement System (PhilGEPS), Procuring Entity’s website and conspicuous places. The following shall form an integral part of the Bidding Documents:

From	To
<p>Clause 2.1 of Section II Instruction to Bidders</p> <p>The GOP through the source of funding as indicated below for General Appropriations Act of 2021 in the amount of Two Million Seven Hundred Thousand Pesos (Php 2,70,000.00).</p>	<p>Clause 2.1 of Section II Instruction to Bidders</p> <p>The GOP through the source of funding as indicated below for General Appropriations Act of 2021 in the amount of Two Million Seven Hundred Thousand Pesos (Php <u>2,700,000.00</u>).</p>
<p>Item No. 2 of Section VI Technical Specifications</p> <p>Two (2) units Mechanical Dryer</p> <ul style="list-style-type: none"> • Capacity: min. 100 to 120 kg per batch; • Heating capacity: 11 kg; • Cooling capacity: 8 kg; • Dehydration rate: 10 L/hr; • Moisture capacity: 20 L/hr; • Rated temperature: 75°C; • Maximum temperature: 80°) • Power Requirement: Input power: 4.8 kW; 220 V / 50-60 Hz / Single Phase • Drying time: 3 hours in average 	<p>Item No. 2 of Section VI Technical Specifications</p> <p>Two (2) units Mechanical Dryer</p> <ul style="list-style-type: none"> • Capacity: min. 100 to 120 kg per batch; • Heating capacity: 11 kg; • Cooling capacity: 8 kg; • Dehydration rate: 10 L/hr; • Moisture capacity: 20 L/hr; • Rated temperature: 75°C; • <u>Maximum temperature: 80°C;</u> • Power Requirement: Input power: 4.8 kW; 220 V / 50-60 Hz / Single Phase • Drying time: 3 hours in average
<p>Item No. 4 of Section VI Technical Specifications</p> <p>Two (2) units Roasting Machine</p> <ul style="list-style-type: none"> • Capacity: 10-12 kg/load • Power Requirements: 1.5kW/220v/60Hz • Material: 304 stainless steel • Blade: Steel Blade • Fuel Source: dual (electric and LPG) • Dimension: 1200x470x950mm (LxWxH) or Manufacturer’s standard 	<p>Item No. 4 of Section VI Technical Specifications</p> <p>Two (2) units Roasting Machine</p> <ul style="list-style-type: none"> • Capacity: 10-12 kg/load • Power Requirements: 1.5kW/220v/60Hz • Material: 304 stainless steel • Blade: Steel Blade • <u>Power Source: electric</u> • Dimension: 1200x470x950mm (LxWxH) or Manufacturer’s standard

<p>Item No. 10 of Section VI Technical Specifications</p> <p>Two (2) Chocolate Melanger with Speed Controller</p> <ul style="list-style-type: none"> • Powerful motor: 0.25 HP (about 200 watts). • CE rated motor; Voltage: 220 - 240 volts, 50-60 Hz; • Capacity (minimum requirement) 10 lbs, • Full drum volume: 8 litres; • Dimensions: Manufacturer's standard 	<p>Item No. 10 of Section VI Technical Specifications</p> <p>Two (2) Chocolate Melanger with Speed Controller</p> <ul style="list-style-type: none"> • <u>Motor: 0.25 HP (about 200 watts).</u> • CE rated motor; Voltage: 220 - 240 volts, 50-60 Hz; • Capacity (minimum requirement) 10 lbs, • Full drum volume: 8 litres; • Dimensions: Manufacturer's standard
<p>Item No. 19 of Section VI Technical Specifications</p> <p>One (1) unit Spray Dryer Machine</p> <p>Features: High pressure pump/plunger pump, Evaporation Rate: 5-6 kg of water/hour, Product Capacity 60 Liters, Temperature Sensor: Type K Thermocouple, Temperature Gauge: Delta DTB Series or any similar temperature gauge, Fuel: LPG inclusive of LPG Tank 50Kg with regulator, Suction Blower: 3 hp, Feed Delivery plunger pump: 5-HP, Operating cycle: Batch Type, Type of Nozzle Spray: Single Fluid System, Material of Construction: SS 304</p>	<p>Item No. 19 of Section VI Technical Specifications</p> <p>One (1) unit Spray Dryer Machine</p> <ul style="list-style-type: none"> • Features: High pressure pump/plunger pump, • Evaporation Rate: 5-6 kg of water/hour, • <u>Product Capacity: at least 24 liters</u> • Temperature Sensor: Type K Thermocouple, • Temperature Gauge: Delta DTB Series or any similar temperature gauge, • <u>Power Source: LPG inclusive of LPG Tank 50Kg with regulator or electric</u> • <u>Suction Blower: 2-3 HP, 220V, 1-phase, 60Hz;</u> • <u>Feed Delivery plunger pump: 2-3 HP,</u> • Operating cycle: Batch Type, • <u>Type of Nozzle Spray: Single Fluid System or centrifugal atomizer</u> • Material of Construction: SS 304

For guidance and information of all concerned.


(Sgd.) MARY ANN C. DY
 Chairperson, Bids and Awards Committee